

Chamber module LW 1000 floor slab Access LW 600, 880-1129 mm, Class D



Article information

Item no.: 8740013 GTIN: 4026092065280 Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet installation is equipped with all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, a taper, upper section and cover.

Variant

Note on installation depth: A load distribution slab must be installed on site for

load class D

General characteristics

Colour: black
Material: PE-HD
Standard: EN 13598-2

Installation situation: underground installation

Delivery state: Partly for on-site assembly (access steps have been

pre-mounted in the factory)

Approval: Z-42.1-527

Dimensions

Net weight: 108,5 kg
Gross weight: 125 kg
Groundwater resistant from lower edge of base 3000 mm

section:

Installation depth: 880 - 1129 mm

Type of height adjustability: vertically adjustable upper section

Length: 1200 mm



Width: 1200 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Inlet max. scoring (DN): 150 mm
Clear width of tank (LW): 1000 mm
Clear width of entry (LW): 600 mm

Coverage features

Type of cover: Round cover plate

Cover material:

Colour of cover:

Width of cover:

Height of cover:

Length of cover:

Surface:

Corey iron

659 mm

659 mm

Grey iron

659 mm

Grey iron

Locking:

Load class: D 400 (EN 124)

Tightness: surface water resistant