


## Chamber module LW 1000 floor slab Access LW 800, 3646-3895 mm, Class A 15



### Article information

Item no.: 8740082  
 GTIN: 4026092065976  
 Price group: 60

### Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

### Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

#### General characteristics

Colour:	black
Material:	PE-HD
Standard:	EN 13598-2
Installation situation:	underground installation
Delivery state:	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Approval:	Z-42.1-527

#### Dimensions

Net weight:	252 kg
Gross weight:	285 kg
Groundwater resistant from lower edge of base section:	3000 mm

Installation depth: 3646 - 3895 mm  
Type of height adjustability: vertically adjustable upper section  
Length: 1200 mm  
Width: 1200 mm  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

Tank/drain body  
Inlet max. scoring (DN): 150 mm  
Clear width of tank (LW): 1000 mm  
Clear width of entry (LW): 800 mm

#### Coverage features

Type of cover: Rectangular cover plate  
Cover material: Stainless steel  
Width of cover: 950 mm  
Height of cover: 44 mm  
Length of cover: 950 mm  
Surface: anti-slip  
Locking: screwed  
Load class: A 15 (EN 124)  
Tightness: surface water resistant