

Chamber module LW 1000 floor slab Access LW 800, 638-887 mm, K 3, wa.co.



Article information

Item no.: 8740222 GTIN: 4026092093184 Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

General characteristics

Colour: black
Material: PE-HD
Standard: EN 13598-2

Installation situation: floor slab installation

Delivery state: Partly for on-site assembly (access steps have been

pre-mounted in the factory)

Approval: Z-42.1-527

Dimensions

Net weight:92,25 kgGross weight:108,75 kgGroundwater resistant from lower edge of base3000 mm

section:

Diameter: 960 mm Installation depth: 638 - 887 mm

Type of height adjustability: vertically adjustable upper section

Length: 1200 mm
Width: 1200 mm
Packaging dimension: length
Packaging dimension: width



Packaging dimension: height

Tank/drain body

Inlet max. scoring (DN): 150 mm
Clear width of tank (LW): 1000 mm
Clear width of entry (LW): 800 mm

Coverage features

Type of cover: Round cover plate Cover material: Stainless steel

Height of cover: 19 mm
Surface: anti-slip
Locking: screwed

Load class: K 3 (EN 1253-1)

Tightness: surface water resistant