


Pumping station Aquapump XL Duo, SPF 1400-S1





Article information

Item no.: 8742008 GTIN: 4026092068632

Price group: 60

Advantages

- Maximum safety
- Flexible installation
- Hygienic advantages for maintenance and repair

Description

The pumping station for wastewater with and without sewage is equipped with one or two submersible pumps, a backflow preventer and a shut-off valve for the pressure pipe. The collection tank made of permanently resistant polymer (PE) has a closed pump tank (dry installation) with a screwed-on access cover. The station is controlled by a user-friendly control unit, which is optionally integrated in the building management system via a potential-free contact. Alternatively, alarm and collective fault messages can be output via a GSM interface. The KESSEL modular system provides different upper sections and engineering chamber options as accessories.

Variant

Note on installation depth: Version for deeper installation

Type of system: duo pump

Shut-off valve: Shut-off valve made of polymer

Access steps: yes

Installation: Dry installation
Pump control: Control unit
Backflow preventer: integrated
Pressure pipe connection: horizontal

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage



Installation situation: underground installation

Delivery state: Pre-mounted for final assembly on site (pumps and

sensor system must be fitted on site and control

unit must be connected)

Approval: Z-42.1-527

System type: Duo

Dimensions

Net weight:141,5 kgGross weight:159,2 kgGroundwater resistant from lower edge of base3000 mm

section:

Length:1295 mmWidth:1295 mmHeight:1403 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Pressure pipe connection (DN): 80
Pressure pipe connection (OD): 90 mm
Venting connection (DN): 70

Distance from centre of outlet pipe to tank 1300 mm

bottom:

Distance pipe bottom inlet to tank bottom: 753 mm
Distance from centre of inlet pipe to tank 833 mm

bottom:

Distance from inlet pipe invert to top of tank: 650 mm Inlet nominal size (DD): 160 mm Inlet nominal size (DN): 150 mm

Number of inlets: 1

Clear width of tank (LW): 1000 mm Pumping volume: 160 l
Tank volume: 335 l

Pumping device

Pump: SPF 1400-S1

Number of pumps:2Weight, pump:28 kgConnection type:coded plug

Protection class:
Insulation class:
Cos phi - power factor:

I power factor:
F

Protection class (pump): IP 68 (3m/48h) Temperature monitoring: integrated

Max. temperature (permanent) of conveyed 40 °C

material:

Max. pumping capacity: 38 m³/h Max. pumping height: 7 m



Speed: 1420 U/min
Power P1: 1,6 kW
Power P2: 1,1 kW
Operating mode: S1

Type of pump connection cable: H07RN-F 3G 1.5 mm² Impeller type: Multi-vane impeller

Free passage: 40 mm
Length of mains cable for pump: 10 m
Rated current: 7,3 A

Control

Self-diagnosis system (SDS):

Control unit: Comfort

Alarm sensor: Immersion pipe Immersion pipe Level measurement instrument: pneumatic Type of level measurement: IP 54 Protection class control unit: Operating voltage: 230 V Connection type: coded plug Length of mains cable for control unit: 1,4 m Potential-free contact: optional GSM interface: yes USB interface: yes Log book function: yes Multi-line display: yes Battery buffering: yes

yes