

## Sampling chamber LW 400, DN 100/150, class D



### Article information

Item no.: 915880D  
GTIN: 4026092025062  
Price group: 60

### Description

Sampling chamber LW 400 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

#### General characteristics

Colour: black  
Material: PE

#### Dimensions

Net weight:	39 kg
Gross weight:	45 kg
Vertical drop between inlet and outlet:	120 mm
Installation depth:	400 - 1300 mm
Type of height adjustability:	vertically adjustable upper section
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Tank/drain body

Distance pipe bottom inlet to tank bottom:	120 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Clear width of tank (LW):	400 mm

#### Coverage features

Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Load class:	D 400 (EN 124)

Tightness:

odour-tight and surface water resistant