

Sampling chamber d: 450 mm, DN 100, Class D



Article information

Item no.: 915881D
GTIN: 4026092055410
Price group: 60

Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

General characteristics

Colour: black
Material: PE

Dimensions

Net weight:	47 kg
Gross weight:	53 kg
Vertical drop between inlet and outlet:	160 mm
Installation depth:	950 - 1300 mm
Type of height adjustability:	vertically adjustable upper section
Length:	730 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Distance pipe bottom inlet to tank bottom:	205 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Clear width of tank (LW):	450 mm

Coverage features

Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black

Load class:

Tightness:

D 400 (EN 124)

odour-tight and surface water resistant