

Sampling chamber DN 150, Class B



Article information

Item no.: 915882B
 GTIN: 4026092048535
 Price group: 60

Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length.

| | |
|--|-------------------------------------|
| Flow direction: | straight |
| General characteristics | |
| Colour: | black |
| Material: | PE |
| Dimensions | |
| Net weight: | 30 kg |
| Gross weight: | 37 kg |
| Vertical drop between inlet and outlet: | 160 mm |
| Installation depth: | 950 - 1300 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Length: | 730 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Distance pipe bottom inlet to tank bottom: | 205 mm |
| Outlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 150 mm |
| Inlet nominal size (OD): | 160 mm |
| Inlet nominal size (DN): | 150 mm |
| Clear width of tank (LW): | 450 mm |
| Coverage features | |
| Type of cover: | Cover plate |
| Cover material: | Grey iron |
| Colour of cover: | black |
| Load class: | B 125 (EN 124) |

Tightness:

odour-tight and surface water resistant