



Grease separat. EasyClean Modular free, NS 3, Standard, 2-part







Article information

Item no.: 93003-R GTIN: 4026092071243

Price group: 60

Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Chamber system: two-piece chamber

Disposal variant: Standard

Shredder-Mix-System: no
Inspection window: no
Nominal size (NS): 3
SonicControl: no
Refill inlet in accordance with DIN 1988: no

Type of disposal: manual with suction hose

General characteristics

Material: PE

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)



Dimensions

60 kg Net weight: Gross weight: 60 kg Diameter: 630 mm Height tank bottom up to centre section: 650 mm Height centre section to top edge of tank: 690 mm Set-up area, height: 1395 mm Required access area, length: 1100 mm Required access area, width: 1020 mm Required access area, height: 690 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Distance pipe bottom outlet to tank bottom: 1020 mm
Distance pipe bottom inlet to tank bottom: 1090 mm
Outlet nominal size (OD): 110 mm
Outlet nominal size (DN): 100 mm
Inlet nominal size (OD): 110 mm
Inlet nominal size (DN): 100 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover
Cover material: Polymer
Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents:300 lTotal volume:600 lContents of sludge trap:300 lStorage quantity of grease:120 l

Control

Control unit: no