

Grease separator EasyClean free NS 7, Standard, Ref. in., Insp. Win., SC



Article information

Item no.: 93007.32
GTIN: 4026092063453
Price group: 60

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:	Standard
Shredder-Mix-System:	no
Inspection window:	yes
Nominal size (NS):	7
SonicControl:	yes
Refill inlet in accordance with DIN 1988:	yes
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3

General characteristics

Material:	PE
Installation situation:	free-standing installation
Delivery state:	Installation-ready (connection parts must be connected on site)

Dimensions

Net weight:	158 kg
Gross weight:	188 kg
Set-up area, length:	2147 mm
Set-up area, width:	948 mm

Set-up area, height:	1653 mm
Required access area, length:	1910 mm
Required access area, width:	948 mm
Required access area, height:	1653 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150 mm
Inlet nominal size (OD):	160 mm
Inlet nominal size (DN):	150 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	650 l
Total volume:	1350 l
Contents of sludge trap:	700 l
Storage quantity of grease:	280 l
Control	
Control unit:	no