


Grease separator EasyClean free NS 15, Direct, left





Article information

Item no.: 93015-01-D-L GTIN: 4026092105191 Price group: 60

Advantages

- Inspection window and Refill inlet as standard
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odourreduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

left
no
yes
15
no
yes
manual
PE
free-standing installation
Installation-ready (connection parts must be
connected on site)
Storz-B coupling R 2 1/2" for disposal vehicle
connection



Dimensions	
Net weight:	360 kg
Gross weight:	435 kg
Set-up area, length:	3530 mm
Set-up area, width:	1490 mm
Set-up area, height:	1950 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
	lioight
Tank/drain body	
Nominal pressure (PN):	10
Pressure pipe connection (DN):	65
Pressure pipe connection (DD):	75 mm
Distance pipe bottom outlet to tank bottom:	1130 mm
Distance pipe bottom inlet to tank bottom:	1200 mm
Outlet nominal size (OD):	200 mm
Outlet nominal size (DN):	200 mm
Inlet nominal size (OD):	200 mm
Inlet nominal size (DD):	200 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Sorvicing opening:	420 mm
Servicing opening:	42011111
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
	Quick-release closure
Locking: Tightness:	-
lightness.	odour-tight
Wastewater contents	
Separator contents:	2230 l
Total volume:	3730 l
Storage quantity of grease:	600 L
Stolage quality of glease.	0001
Control	
Control unit:	no
Controcumit.	