

Grease separator EasyClean free NS 25, Direct



Article information

Item no.: 93025-06-D GTIN: 4026092103159

Price group: 60

Advantages

- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odourreduced manual disposal. 20 year polyethylene warranty.

Variant

Disposal variant: Direct Shredder-Mix-System: no Inspection window: no Nominal size (NS): 25 SonicControl: no Refill inlet in accordance with DIN 1988: no manual Type of disposal: Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PΕ Standard: FN 1825

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Storz-B coupling R 2 1/2" for disposal vehicle Scope of delivery:

connection

Dimensions

Net weight: 517 kg Gross weight: 517 kg Set-up area, length: 5140 mm Set-up area, width: 1280 mm



Set-up area, height: 1625 mm Required access area, length: 5140 mm Required access area, width: 1280 mm Required access area, height: 1625 mm Length: 5140 mm Width: 1600 mm Height: 1625 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Nominal pressure (PN): 10 Pressure pipe connection (DN): 65 Pressure pipe connection (OD): 75 mm Distance pipe bottom outlet to tank bottom: 1030 mm Distance pipe bottom inlet to tank bottom: 1100 mm Outlet nominal size (OD): 200 mm Outlet nominal size (DN): 200 mm Inlet nominal size (OD): 200 mm Inlet nominal size (DN): 200 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 2050 l
Total volume: 4550 l
Contents of sludge trap: 2500 l
Storage quantity of grease: 1000 l

Control

Control unit: no