


Grease separator EasyClean free NS 25, Auto Mix & Pump





Article information

Item no.: 93025-06-PVS GTIN: 4026092103265

Price group: 60

Advantages

- Clean and odour-free disposal and cleaning
- Customisation possible through control unit
- Clean and odour-free disposal and cleaning

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. The innovative Shredder-Mix-System with integrated macerating system is responsible for homogenising and circulating the tank contents. Cleaning and odour-neutral disposal takes place via an exterior pump with 2-way valve and actuator which can be disconnected from the tank by a shut-off valve. The fully automatic program run is controlled by a user-friendly control unit with multi-line display that can be integrated into the building management system through a potential-free contact. Cleaning and disposal can be started remotely using the remote control, which is available as an option. Thanks to the customisable cleaning program with fast-selection function, cleaning can be adapted to the local circumstances as required. Observance of the Drinking Water Hygiene Directive can be guaranteed through the fully automatic rinsing of the drinking water pipes. 20 year polyethylene warranty.

Variant

Shut-off valve: ves

Disposal variant: Auto Mix & Pump

Shredder-Mix-System: yes Inspection window: yes Nominal size (NS): 25 SonicControl: no



Disposal system: Disposal pump

Refill inlet in accordance with DIN 1988: yes

Type of disposal: automatic disposal and cleaning system

Water supply: 2 solenoid valves 1"

Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PE Standard: EN 1825

Installation situation: free-standing installation

Delivery state: Installation-ready (electrical components,

connection parts must be connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle

connection

Dimensions

Net weight: 650 kg Gross weight: 650 kg Diameter: 630 mm Set-up area, length: 5140 mm Set-up area, width: 1600 mm Set-up area, height: 1625 mm Required access area, length: 5140 mm Required access area, width: 1280 mm Required access area, height: 1625 mm Length: 5140 mm Width: 1600 mm 1625 mm Height: Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Nominal pressure (PN): 10 Pressure pipe connection (DN): 65 Pressure pipe connection (OD): 75 mm Distance pipe bottom outlet to tank bottom: 1030 mm Distance pipe bottom inlet to tank bottom: 1100 mm Outlet nominal size (OD): 200 mm Outlet nominal size (DN): 200 mm Inlet nominal size (OD): 200 mm Inlet nominal size (DN): 200 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover
Cover material: Polymer
Colour of cover: black

Locking: Quick-release closure



odour-tight Tightness:

Wastewater contents

2050 l Separator contents: Total volume: 4550 l 2500 l Contents of sludge trap: Storage quantity of grease: 1000 l

Pumping device

Pump: SPF 300 KE 2.0

Number of pumps: 2 Weight, pump: 44 kg

Connection type: Direct connection

Protection class: Insulation class: 0,87 Cos phi - power factor: Protection class (pump): IP 55 Temperature monitoring: integrated 40°C

Max. temperature (permanent) of conveyed

material:

Max. pumping capacity: 60 m³/h Max. pumping height: 17 m

Speed: 2850 U/min Power P1: 3.6 kW Power P2: 3 kW

Operating mode: S2 - 30 min.

Type of pump connection cable: H07RN-F 7G 1.5 mm²

Impeller type: Radial impeller with macerating system

Length of mains cable for pump: 5 m Rated current: 6,2 A

Control

Control unit: yes Motor protection switch: yes Type of fuse required (RCD): 30 mA Protection class control unit: **IP 54** Mains frequency: 50 Hz Operating voltage: 400 V

Connection type: Direct connection

Potential-free contact: yes GSM interface: no USB interface: yes Log book function: yes Multi-line display: yes Battery buffering: no Self-diagnosis system (SDS): ves

Type of fuse required (control unit): Fuse protection through control unit 400 V