

## Grease separator EasyClean free NS 25, Standard



## **Article information**

Item no.: 93025-06 GTIN: 4026092103142 Price group: 60

## **Advantages**

- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

## **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:

Shredder-Mix-System:

Inspection window:

Nominal size (NS):

SonicControl:

Refill inlet in accordance with DIN 1988:

Standard

no

no

no

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PE Standard: EN 1825

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

**Dimensions** 

Net weight: 445 kg
Gross weight: 445 kg
Diameter: 630 mm
Set-up area, length: 5140 mm
Set-up area, width: 1280 mm
Set-up area, height: 1625 mm



Required access area, length: 5140 mm Required access area, width: 1280 mm Required access area, height: 1625 mm Length: 5140 mm Width: 1600 mm 1625 mm Height: Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (OD):

200 mm

Inlet nominal size (DN):

200 mm

200 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 2050 l
Total volume: 4550 l
Contents of sludge trap: 2500 l
Storage quantity of grease: 1000 l

Control

Control unit: no