


Grease separator EasyClean ground NS 1, Direct, 1040-1740 mm, A/B, left





Article information

Item no.: 95010-170B-DL GTIN: 4026092101100

Price group: 60

Advantages

- Low odour and clean disposal
- Defined disposal point
- Complete emptying of the separator

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic structural components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap, and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via a service access cover. A direct disposal pipe socket is available for manual disposal. A load distribution slab must be installed on site for load class D. The reinforcement drawings are part of the EBA and are available from KESSEL. The tank is groundwater resistant up to ground level (GL). 20 year polyethylene warranty.

Variant

Note on installation depth: Ground installation frost-free depth 1700 mm

Direction of flow: left
Disposal variant: Direct
Nominal size (NS): 1

Disposal system:

Type of disposal:

Load-bearing capacity (DIN 19901):

Disposal pipe manual

E4

General characteristics

Material: PE Standard: EN 1825

Installation situation: underground installation



Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight: 245 kg
Gross weight: 245 kg
Diameter: 648 mm

Installation depth: 1040 - 1740 mm

Length:1700 mmWidth:1090 mmHeight:1515 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Distance pipe bottom outlet to tank bottom: 800 mm
Distance pipe bottom inlet to tank bottom: 870 mm
Outlet nominal size (DN): 100 mm
Inlet nominal size (DD): 110 mm
Inlet nominal size (DN): 100 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG

pipes in accordance with DIN 19534, PP or AS

Clear width of entry (LW): 600 mm

Coverage features

Type of cover:

Cover plate
Cover material:

Grey iron
Colour of cover:

black
Locking:

Lock & Lift
Load class:

B 125 (EN 124)

Tightness: odour-tight and surface water resistant

Wastewater contents

Separator contents: 550 l
Max. grease layer thickness: 42 mm
Total volume: 650 l
Contents of sludge trap: 100 l
Storage quantity of grease: 40 l