


## Grease seperator EasyClean ground NS 1, Standard, 1190-1740 mm, Class D





## **Article information**

Item no.: 95010-170D GTIN: 4026092100547

Price group: 60

## **Advantages**

- Vertically adjustable upper section with odourtight cover plates in various load classes
- Resistant to groundwater
- Low-maintenance operation

## **Description**

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic structural components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via a service access cover.

Manual disposal is carried out with the tank open.

A load distribution slab must be installed on site for load class D. The reinforcement drawings are part of the EBA and are available from KESSEL.

The tank is groundwater resistant up to ground level (GL). 20 year polyethylene warranty.

Variant

Note on installation depth: Ground installation frost-free depth 1700 mm

Disposal variant: Standard

Shredder-Mix-System: no
Inspection window: no
Nominal size (NS): 1
SonicControl: no
Refill inlet in accordance with DIN 1988: no

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): E4



General characteristics

Material: PE Standard: EN 1825

Installation situation: underground installation

Delivery state: Installation-ready (connection parts must be

connected on site)

**Dimensions** 

Net weight: 240 kg Gross weight: 240 kg

Installation depth: 1190 - 1740 mm

Type of height adjustability: vertically adjustable upper section, can be tilted by

5 degrees

Length:1700 mmWidth:1090 mmHeight:1515 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (OD):

110 mm
Inlet nominal size (DN):

110 mm
Inlet nominal size (DN):

100 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG

pipes in accordance with DIN 19534, PP or AS

Clear width of entry (LW): 600 mm

Coverage features

Type of cover:

Cover plate
Cover material:

Colour of cover:

black
Locking:

Lock & Lift
Load class:

D 400 (EN 124)

Tightness: odour-tight and surface water resistant

Wastewater contents

Separator contents: 550 l
Max. grease layer thickness: 42 mm
Total volume: 650 l
Contents of sludge trap: 100 l
Storage quantity of grease: 40 l

Control

Control unit: no