


Grease separator EasyClean ground NS 7, Direct, 715-1215 mm, A/B, right





Article information

Item no.: 95070-120B-DR GTIN: 4026092100660

Price group: 60

Advantages

- Low odour and clean disposal
- Defined disposal point
- Complete emptying of the separator

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic structural components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap, and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via a service access cover. A direct disposal pipe socket is available for manual disposal. A load distribution slab must be installed on site for load class D. The reinforcement drawings are part of the EBA and are available from KESSEL. The tank is groundwater resistant up to ground level (GL). 20 year polyethylene warranty.

Variant

Note on installation depth: Installation in the ground, frost-free depth 1200 mm

Direction of flow:rightDisposal variant:DirectNominal size (NS):7

Disposal system:

Type of disposal:

Load-bearing capacity (DIN 19901):

Disposal pipe manual

E4

General characteristics

Material: PE Standard: EN 1825

Installation situation: underground installation



Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight: 310 kg Gross weight: 315 kg Diameter: 648 mm Installation depth: 715 - 1215 mm Length: 1870 mm Width: 1090 mm Heiaht: 2375 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (DN):

Inlet nominal size (DD):

Inlet nominal size (DN):

160 mm

Inlet nominal size (DN):

150 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG

pipes in accordance with DIN 19534, PP or AS

Clear width of entry (LW): 600 mm

Coverage features

Type of cover:

Cover plate
Cover material:

Colour of cover:

black
Locking:

Lock & Lift
Load class:

B 125 (EN 124)

Tightness: odour-tight and surface water resistant

Wastewater contents

Separator contents:930 lMax. grease layer thickness:270 mmTotal volume:1630 lContents of sludge trap:700 lStorage quantity of grease:280 l