


Grease separator EasyClean ground NS 8,5, Direct, 665-1165 mm, A/B, left





Article information

Item no.: 95085-120B-DL GTIN: 4026092100998

Price group: 60

Advantages

- Low odour and clean disposal
- Defined disposal point
- Complete emptying of the separator

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic structural components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap, and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via a service access cover. A direct disposal pipe socket is available for manual disposal. A load distribution slab must be installed on site for load class D. The reinforcement drawings are part of the EBA and are available from KESSEL. The tank is groundwater resistant up to ground level (GL). 20 year polyethylene warranty.

Variant

Note on installation depth: Installation in the ground, frost-free depth 1200 mm

Direction of flow:leftDisposal variant:DirectNominal size (NS):8,5

Disposal system:
Type of disposal:
Load-bearing capacity (DIN 19901):
Disposal pipe manual
E4

General characteristics

Material: PE Standard: EN 1825

Installation situation: underground installation



Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight:310 kgGross weight:315 kgDiameter:648 mm

Installation depth: 665 - 1165 mm
Length: 1870 mm
Width: 1150 mm
Height: 2375 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (DN):

Inlet nominal size (DD):

Inlet nominal size (DN):

150 mm

Inlet nominal size (DN):

150 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG

pipes in accordance with DIN 19534, PP or AS

Clear width of entry (LW): 600 mm

Coverage features

Type of cover:

Cover plate
Cover material:

Grey iron
Colour of cover:

black
Locking:

Lock & Lift
Load class:

B 125 (EN 124)

Tightness: odour-tight and surface water resistant

Wastewater contents

Separator contents: 850 l

Max. grease layer thickness: 325 mm

Total volume: 1700 l

Contents of sludge trap: 850 l

Storage quantity of grease: 340 l