


## Grease seperator EasyClean ground NS 10, Standard, 880-1170 mm, Class D





## **Article information**

Item no.: 95100-120D GTIN: 4026092100448

Price group: 60

## **Advantages**

- Vertically adjustable upper section with odourtight cover plates in various load classes
- Resistant to groundwater
- Low-maintenance operation

## **Description**

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic structural components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via a service access cover.

Manual disposal is carried out with the tank open.

A load distribution slab must be installed on site for load class D. The reinforcement drawings are part of the EBA and are available from KESSEL.

The tank is groundwater resistant up to ground level (GL). 20 year polyethylene warranty.

Variant

Note on installation depth: Installation in the ground, frost-free depth 1200 mm

Disposal variant: Standard

Shredder-Mix-System: no
Inspection window: no
Nominal size (NS): 10
SonicControl: no
Refill inlet in accordance with DIN 1988: no

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): E4



General characteristics

Material: PE Standard: EN 1825

Installation situation: underground installation

Delivery state: Installation-ready (connection parts must be

connected on site)

**Dimensions** 

Net weight: 345 kg Gross weight: 350 kg

Installation depth: 880 - 1170 mm

Type of height adjustability: vertically adjustable upper section, can be tilted by

5 degrees

Length:1870 mmWidth:1090 mmHeight:2795 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (OD):

Inlet nominal size (DN):

Inlet nominal size (DN):

150 mm

Inlet nominal size (DN):

150 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG

pipes in accordance with DIN 19534, PP or AS

Clear width of entry (LW): 600 mm

Coverage features

Type of cover:

Cover plate
Cover material:

Colour of cover:

black
Locking:

Lock & Lift
Load class:

D 400 (EN 124)

Tightness: odour-tight and surface water resistant

Wastewater contents

Separator contents: 1100 l
Max. grease layer thickness: 385 mm
Total volume: 2100 l
Contents of sludge trap: 1000 l
Storage quantity of grease: 400 l

Control

Control unit: no