

## EasySink sediment separator free, NS 2



## **Article information**

Item no.: 97202/000 GTIN: 4026092026885

Price group: 60

## **Advantages**

- Waterproof and resistant to aggressive wastewater
- Odour-tight tank
- Low-maintenance operation

## **Description**

The sediment separator is suitable for exposed installation in frost-protected rooms. The collection tank is equipped with a removable sediment tank (NS 2 with two sediment tanks) both made of permanently resistant polymer (PE). An odour trap is installed in the outlet. An odour-tight cover with quick-release closure makes easy access possible for cleaning and maintenance work. 20 year polyethylene warranty.

Variant

Nominal size (NS): 2,00

Type of disposal: manual with suction hose

General characteristics

Material: PE

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Wastewater-resistant: resistant to aggressive wastewater

Odour trap: included

**Dimensions** 

Net weight: 50,65 kg Gross weight: 59,45 kg Set-up area, length: 985 mm 650 mm Set-up area, width: 598 mm Set-up area, height: Required access area, length: 800 mm Required access area, width: 650 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height



Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

To mm

Inlet nominal size (DN):

70 mm

Inlet nominal size (DN):

70 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG

pipes in accordance with DIN 19534, PP or AS

Volume of collecting tank: 51 l

Coverage features

Type of cover:

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Cover

630 mm

Locking: Quick-release closure

Tightness: odour-tight

Control

Control unit: no