

Pump system Aquapump Retrofit Tronic, GTK3700-S1, level sensor



Article information

Item no.: GTK3700-M

GTIN:

Price group: 60

Description

Pump system, wet installation, for installation in an on-site chamber module.

- For wastewater with and without sewage (not approved for use in an ATEX zone)
- Pressure pipe, pre-assembled at the factory, with mounting parts, a backflow preventer and shut-off valve
- Pump with a single-vane impeller for optimum energy efficiency
- Including a level probe for level measurement Including a KESSEL Aqualift Comfort 400 V control unit User-friendly menu navigation in a multi-line display. With a self-diagnosis system (SDS) and reminder function for the next maintenance. Display of the current measured values. Simple adjustment of the function-related parameters, including an operating hour counter and potential-free contact. Optional forwarding of alarm and collective fault messages via a GSM interface.

- Required minimum diameter of the on-site 1000 mm chamber module:

Variant

Type of system: Single unit Shut-off valve: yes

Pump control: Control unit
Backflow preventer: integrated
Pressure pipe connection: horizontal

General characteristics

Standard: EN 12050-2 as well as EN 12050-1 (without ATEX

requirements)

Type of wastewater: for wastewater with or without sewage (in

installation situations without ATEX requirements)

Installation situation: installation in on-site collecting tank

Delivery state: Modular set for assembly on site



System type: Tronic

Tank/drain body

Pressure pipe connection (DN): 50
Pressure pipe connection (OD): 63 mm

Pumping device

Pump: GTK 3700

Number of pumps: 1
Weight, pump: 12 kg
Connection type: coded plug
Operating voltage: 400 V

Protection class:

Protection class (pump): IP 68 (3m)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed 40 °C

material:

Max. pumping capacity:

Max. pumping height:

Speed:

Power P1:

Power P2:

Operating mode:

82 m³/h

23,5 m

2900 U/min

3,7 kW

51

Type of pump connection cable: H07RN-F 7G 1.5 mm² Impeller type: Single-vane impeller

Length of mains cable for pump: 10 m Rated current: 6,5 A

Control

Control unit: Comfort Level sensor Alarm sensor: Level measurement instrument: Level sensor Type of level measurement: hydrostatic Protection class control unit: **IP 54** 50 Hz Mains frequency: 400 V Operating voltage: Connection type: coded plug Length of mains cable for control unit: 1,4 m Potential-free contact: optional GSM interface: yes USB interface: yes Log book function: yes Multi-line display: yes Battery buffering: yes Self-diagnosis system (SDS): yes 3 x C 32 A Type of fuse required (control unit):